



4460 S WINDERMERE ST
 ENGLEWOOD, CO 80110
 P: 303.761.3058
 F: 303.783.9014
 W: CHIMFG.COM
 E: CHIMFG@AOL.COM



HETOD WITH DAMPER

HETOD (With Damper)					
ORDER SIZE	A	B	C	D	E
4"	X	X	1.2	9"	26
6"	12"	6"	1.7	9"	26
7"	11"	5"	2	10"	26
8"	12"	6"	2.2	9"	26
9"	14"	6"	2.6	10"	26
10"	16"	7"	3.2	11"	26
12"	18"	8"	3.9	11"	26
14"	20"	9"	4.3	11"	26
16"	20"	12"	5.9	14"	24
18"	26"	14"	7.3	14"	24
20"	26"	14"	7.8	14"	24

A=Weight
 B=Gauge
 C=Weight
 D=Length (from bead to flange out)
 E=Gauge

CONSTRUCTED:

Hot Dipped Galvanized Steel PER ASTM A653 CS Type B

APPLICATIONS:

Commercial designed to meet SMACNA Duct Construction Standards. Maximum W.G. is 2"- 4".

DESCRIPTION:

All HETO'S are made with the finest G60 American Steel. Pop riveted seams. The collar is crimped the square side has 1" flange out with gasket for a sealed connection and faster installation times. It's 45° angle allows for better air flow.

DAMPER: 26 GAUGE - 1 SPRING/SOLID BEARING, 1 HANDLE, 2 WING NUTS

UNION MADE IN THE UNITED STATES OF AMERICA
 PROUDLY USING 100% AMERICAN MADE METALS MANUFACTURED BY LUKJAN