



4460 S WINDERMERE ST
 ENGLEWOOD, CO 80110
 P: 303.761.3058
 F: 303.783.9014
 W: CHIMFG.COM
 E: CHIMFG@AOL.COM



REDUCER CAP

ORDER SIZE	A	B	C
7" X 5"	1"	0.9	26
7" X 6"	1½"	0.9	26
8" X 6"	1"	1	26
8" X 7"	2"	1.1	26
9" X 6"	2"	1.1	26
9" X 7"	3½"	1.1	26
9" X 8"	2"	1.1	26
10" X 6"	3½"	1.3	26
10" X 7"	2"	1.3	26
10" X 8"	3½"	1.3	26
10" X 9"	2"	1.3	26
12" X 6"	2"	1.4	26
12" X 8"	2"	1.5	26
12" X 9"	1½"	1.5	26
12" X 10"	2"	1.6	26

A=Length
 B=Weight
 C=Gauge

CONSTRUCTED:

Hot Dipped Galvanized Steel PER ASTM A653 CS Type B

APPLICATIONS:

Commercial designed to meet SMACNA Duct Construction Standards. Maximum W.G. is 2" - 3".

DESCRIPTION:

All Cap Reducers are made with the finest G60 American Steel. The collars are raw not crimped for your convenience. Pop riveted seams. These are in very tight spaces that have no room to reduce to the desired size and length.

UNION MADE IN THE UNITED STATES OF AMERICA
 PROUDLY USING 100% AMERICAN MADE METALS MANUFACTURED BY MIDWEST DUCTS