

4460 S WINDERMERE ST ENGLEWOOD, CO 80110

P: 303.761.3058 F: 303.783.9014 W: CHIMFG.COM

E: CHIMFG@AOL.COM



# **SPIN SERIES**

ORDER SIZE	PLAIN #951				
	Α	В	C	Е	
4"	6.5"	6"	0.6	26	
5"	7"	6.5"	8.0	26	
6"	8"	6.5"	8.0	26	
7"	9"	6.5"	1	26	
8"	10"	6.5"	1.4	26	
9"	11"	6.5"	1.3	26	
10"	12"	6.5"	1.3	26	
12"	14"	6.5"	1.5	26	
14"	16"	8.25"	1.8	26	
16"	18"	8.25"	1.9	24	
18"	20"	8.25"	2	24	
20"	22"	8.25"	2.1	24	

ORDER SIZE	W/DAMPER #952				
Α	В	С	Е		
4"	8.5"	0.9	26		
5"	8.5"	1.1	26		
6"	8.5"	1.4	26		
7"	8.5"	1.9	26		
8"	8.5"	2	26		
9"	8.5"	2.3	26		
10"	10.25"	2.4	26		
12"	10.25"	3.4	26		
14"	10.25"	5.1	24		
16"	12"	5.3	24		
18"	12"	5.6	24		
20"	12"	6	24		

ORDER SIZE	W/SCOOP & DAMPER #954				
Α	В	С	D	Е	
4"	6"	1.2	3"	26	
5"	7"	1.4	4"	26	
6"	8"	1.8	4"	26	
7"	8.5"	2	4"	26	
8"	8.5"	2.2	5"	26	
9"	8.5"	2.4	5"	26	
10"	10.25"	2.6	6"	26	
12"	10.25"	2.8	7"	26	
14"	10.25"	5.3	8"	24	
16"	12"	5.6	9"	24	
18"	12"	5.8	10"	24	
20"	12"	6.2	11"	24	

A=Width at Base

**B**=Depth at Base

C=Weight

D=Length of scoop into airflow

E=Gauge

## **CONSTRUCTED:**

Hot Dipped Galvanized Steel PER ASTM A653 CS Type B

### **APPLICATIONS:**

Commercial designed to meet SMACNA Duct Construction Standards. Maximum W.G. is positive 2" - 3".

#### **DESCRIPTION:**

All Spins are made with the finest G60 American Steel. Pop riveted seams. The collar is crimped and a deeper bead for faster installation. The conical shape allows for greater air flow.

#### **DAMPERS:**

26 GAUGE - 1 SPRING/SOLID BEARING, 1 HANDLE, 2 WING NUTS